SERIES8 PERFORMANCE VOCALS

CO-8 OMNIDIRECTIONAL





DESCRIPTION

The SERIES**8** omnidirectional collection is offered in 3 popular styles: headset, earworn, and lavalier. The omnidirectional pattern assures ease in fitting with a natural vocal sound well suited in low to moderate noise environments. Its circular pick up pattern adapts exceptionally to a wide array of mic'ing applications. All the SERIES**8** omni microphones offer IP 57 waterproof rating against water, sweat and makeup; and our super bendable boom is "Unbreakable" up to 360°. Each microphone comes with one X-Connector of your choosing for termination to your wireless system. The X-Connectors have a threaded screw connection so they are simple to remove, but remain secure while in use.

Boom Bends 360°	136 dB max SPL	Water, Sweat, Makeup Proof	Interchangeable
360	•)))	5	¢

-XXX CONNECTOR OPTIONS

-XLEw Lectrosonics-waterproof	-XSH Shure, Line 6
-XMP MiPro	-XSK Sennheiser SK, Zaxcom
-XSD Sony DWT-B01	- XTX Telex
-XSE Sennheiser	
	-XMP MiPro -XSD Sony DWT-B01

-XX COLOR OPTIONS


-WH White (lav)	-BE Beige	-BR Brown	-BL Black
-----------------	-----------	-----------	-----------

SPECIFICATIONS

Element:	Waterproof Back Electret Condenser	
Pattern:	Omnidirectional	
Frequency:	20Hz ~ 20kHz	
Sensitivity: Sensitivity (hi):	-43 dB 1V/Pa (Nominal Sensitivity \pm 3 dB at 1kHz) -32 dB 1V/Pa (Nominal Sensitivity \pm 3 dB at 1kHz)	
Maximum SPL: Maximum SPL (hi):	136 dB SPL 118 dB SPL	
Output Impedance:	$1400\Omega \pm 30\%$ (at 1kHz)	
Operating Voltage:	1 ~ 10 V	
Cable Length:	4ft. 077in. + connector	
Net Weight:	0.6 oz	
Colors:	White*, Beige, Brown* or Black (*not available in hi sensitivity)	
X-Connector Options:	TA3F, TA4F, TA5F, lockable 3.5mm, Hirose, Lemo-style	
Boom Flexibility:	Bendable to 360°	
Ear Placement:	Left/Right	
Included Accessories	Windscreen cable clin storage box	

Included Accessories:

1 kHz Polar Response



Windscreen, cable clip, storage box

